

AMENDMENTS TO THE CLAIMS

The following listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Cancelled)

Claim 2 (Previously Presented) A trocar system as recited in Claim 3 wherein the movement of the release member causes the blocking surface to be displaced out of axial alignment with the shield.

Claim 3 (Currently Amended) A trocar system which comprises:

a cannula forming an opening therethrough and having proximal and distal ends, the cannula defining a proximally facing surface; and

an obturator assembly being at least partially insertable within the cannula, the obturator assembly including:

an obturator housing including a base portion having a distally facing end surface configured and dimensioned to facilitate close proximate positioning thereof with the proximally facing surface of the cannula;

a penetrating tip;

an elongated shield including a guard, the penetrating tip and the guard being movable relative to one another, the elongated shield including an extended surface; and

a latch mechanism disposed generally within the obturator housing, which facilitates changing the configuration of the obturator assembly between a fixed-shield orientation, wherein at least a portion of the guard is maintained to extend at least partially distal of the penetrating tip to prevent puncturing of tissue by the penetrating tip, and a non-fixed shield orientation whereby the guard and the penetrating tip are permitted to move relative to one another to facilitate puncturing of tissue by the penetrating tip, the latch mechanism including:

a release member having a button portion and a camming surface; wherein the button portion protrudes at least partially through an opening formed in the distally facing end surface of the obturator housing, the button portion being moveable from a first position extending outwardly from the distally facing end surface of the obturator housing to a second position positioned further within the obturator housing upon engagement with the proximally facing surface of the cannula; and

a latch operatively associated with the release member, the latch having a blocking surface operatively engageable with the elongated shield and a mating surface, the mating surface cooperating with the camming surface of the release member such that application of a proximally directed force to the distal end of the button portion of the release member during engagement with the proximally facing surface of the cannula causes the button portion to move to the second position thereof and causes corresponding movement of the release member whereby the camming surface moves substantially laterally and biases the mating surface to move the latch such that the blocking surface permits relative axial movement of the shield and the penetrating tip, and further wherein upon axial movement of the shield, the extended surface of the shield biases the release member away from the latch to permit the latch to return to an original orientation.

Claim 4 (Previously Presented) A trocar system as recited in claim 3 wherein the latch is biased such that the blocking surface is normally disposed in axial alignment with at least a portion of the shield to prevent axial movement thereof.

Claim 5 (Original) A trocar system as recited in claim 2 wherein the blocking surface is disposed proximal of the at least a portion of the shield.

Claim 6 (Previously Presented) A trocar system as recited in claim 3 wherein the release member is configured and dimensioned such that axial movement of the release member imparts lateral movement of the blocking surface of the latch member.

Claim 7 (Previously Presented) A trocar system as recited in claim 3 wherein the obturator includes a shaft fixed relative to the housing and the penetrating tip is a flat knife blade secured to the shaft.

Claim 8 (Cancelled)

Claim 9 (Previously Presented) A trocar system as recited in claim 3 wherein the guard is configured and dimensioned to completely enclose the penetrating tip.

Claim 10 (Previously Presented) A trocar system as recited in claim 3 wherein the shield and guard are separate elements fitted together during assembly of the obturator.

Claims 11-21 (Cancelled)

Claim 22 (Currently Amended) A trocar system, which comprises:

a cannula defining a longitudinal axis and having a longitudinal opening therethrough; and

an obturator at least partially positionable within the longitudinal opening of the cannula, the obturator including:

an obturator housing;

an obturator shaft extending from the obturator housing and receivable within the cannula sleeve, and having a penetrating member adapted to penetrate tissue;

a guard mounted about the obturator blade, the guard and the obturator shaft being adapted for relative longitudinal movement between a first relative position corresponding to an unarmed condition of the penetrating member and a second relative position corresponding to an armed condition of the penetrating member;

a latch member ~~associated~~ monolithically formed with the obturator housing, the latch member being moveable from an initial position securing the guard and the obturator shaft in the first relative position to a release position permitting the guard and the obturator shaft to move to the second relative position, the latch member arranged within the obturator housing in cantilever relation therewith and being normally biased toward the initial position thereof; and

a release member mounted to the obturator housing and operatively coupled with the latch member, the release member adapted to move the latch member to the

release position during positioning of the obturator within the longitudinal opening of the cannula.

Claim 23 (Previously Presented) The trocar system according to claim 22 wherein the release member is adapted for movement relative to the obturator housing during positioning of the obturator within the longitudinal opening of the cannula, to thereby move the latch member to the release position.

Claim 24 (Previously Presented) The trocar system according to claim 23 wherein the release member includes a release button, the release button dimensioned to extend distally beyond the obturator housing.

Claim 25 (Previously Presented) The trocar system according to claim 24 wherein the cannula includes a cannula housing and a cannula sleeve extending from the cannula housing.

Claim 26 (Previously Presented) The trocar system according to claim 25 wherein the release button is positioned to engage the cannula housing upon mating of the obturator housing and the cannula housing whereby a generally proximally directed force applied by the cannula housing on the release button causes displacement of the release member and movement of the latch member to the release position.

Claim 27 (Previously Presented) The trocar system according to claim 26 wherein the obturator shaft is fixed relative to the obturator housing, and wherein the guard is adapted for longitudinal

movement about the obturator shaft between the first relative position and the second relative position.

Claim 28 (Previously Presented) The trocar system according to claim 27 wherein the latch member includes a locking surface adapted to securely engage a corresponding locking ledge of the guard when the guard is in the first relative position thereby substantially preventing longitudinal movement of the guard to the second relative position thereof.

Claim 29 (Previously Presented) The trocar system according to claim 28 wherein the release member is adapted to move the latch member to cause release of the locking surface with the locking ledge of the guard upon mating of the obturator housing with the cannula housing to thereby permit movement of the guard to the second relative position.

Claim 30 (Previously Presented) The trocar system according to claim 29 wherein the release member includes a camming surface engageable with a corresponding mating surface of the latch member, the camming surface being movable in at least a lateral direction with respect to the longitudinal axis during movement of the release member, to laterally deflect the locking surface of the latch member and cause release thereof with the locking latch of the guard.

Claims 31-33 (Canceled)

Claim 34 (Previously Presented) The trocar system according to claim 27 wherein the guard is normally biased toward the first relative position so as to assume the first relative position upon removal of a proximally directed force thereto.

Claim 35 (Previously Presented) The trocar system according to claim 27 wherein the latch member is adapted to return to the initial position thereof upon removal of the generally proximally directed force on the release button.

Claim 36 (Previously Presented) The trocar system according to claim 27 wherein the penetrating member includes a generally flat blade.

Claims 37-44 (Canceled)